

ABAC SPINN

Teho 2,2 - 5,5 kW
Ilman säiliötä.



Koodi	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
4152008000	SPINN 2.210	230 / 50	-	10	240	2,2 / 3	61	620 x 612 x 995	99	
4152008002	SPINN 310	400 / 50	-	10	320	3 / 4	61	620 x 612 x 995	103	
4152008004	SPINN 410	400 / 50	-	10	470	4 / 5,5	62	620 x 612 x 995	105	
4152008005	SPINN 5.510	400 / 50	-	10	600	5,5 / 7,5	64	620 x 612 x 995	110	

* Varastotuote

ABAC SPINN

Teho 2,2 - 5,5 kW
Säiliöllä



Koodi	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
4152008006	SPINN 2.210 200	230 / 50	200	10	240	2,2 / 3	61	620 x 612 x 995	155	
4152008008	SPINN 310 200	400 / 50	200	10	320	3 / 4	61	620 x 612 x 995	157	
4152008010	SPINN 410 200	400 / 50	200	10	470	4 / 5,5	62	620 x 612 x 995	159	
4152008011	SPINN 5.510 200	400 / 50	200	10	600	5,5 / 7,5	64	620 x 612 x 995	164	

* Varastotuote

KOMPRESSORIT



ABAC SPINN.E

Teho 2,2 - 5,5 kW

Säiliöllä ja kuivaimella.



Koodi	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
4152008027	SPINN.E 2.210 200	230 / 50	200	10	240	2,2 / 3	61	620 x 612 x 995	187	
4152008013	SPINN.E 310 200	400 / 50	200	10	320	3 / 4	61	620 x 612 x 995	191	
4152008015	SPINN.E 410 200	400 / 50	200	10	470	4 / 5,5	62	620 x 612 x 995	193	
4152008016	SPINN.E 5.510 200	400 / 50	200	10	600	5,5 / 7,5	64	620 x 612 x 995	198	

* Varastotuote

ABAC SPINN

Teho 5,5 - 11 kW
Ilman säiliötä.



										
	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
4152008327	SPINN 5510	400 / 50	-	10	630	5,5 / 7,5	65	810 x 650 x 995	156	
4152008359	SPINN 7.510	400 / 50	-	10	920	7,5 / 10	66	810 x 650 x 995	167	
4152008362	SPINN 1110	400 / 50	-	10	1310	11 / 15	68	810 x 650 x 995	180	

* Varastotuote

ABAC SPINN

Teho 5,5 - 11 kW
Säiliöllä



										
	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
4152008328	SPINN 5510 270	400 / 50	270	10	630	5,5 / 7,5	65	810 x 650 x 995	191	
4152008364	SPINN 7.510 270	400 / 50	270	10	920	7,5 / 10	66	810 x 650 x 995	202	
4152008365	SPINN 1110 270	400 / 50	270	10	1310	11 / 15	68	810 x 650 x 995	215	

* Varastotuote

KOMPRESSORIT



ABAC SPINN.E

Teho 5,5 - 11 kW
Säiliöllä ja kuivaimella.



										
	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
4152008332	SPINN.E 5510 270	400 / 50	270	10	630	5,5 / 7,5	65	810 x 650 x 995	219	
4152008072	SPINN.E 7.510 270	400 / 50	270	10	920	7,5 / 10	66	810 x 650 x 995	245	
4152008073	SPINN.E 1110 270	400 / 50	270	10	1310	11 / 15	68	810 x 650 x 995	259	

* Varastotuote

ABAC GENESIS

Teho 5,5 - 15 kW
Säiliöllä ja kuivaimella



Koodi	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
4152009025	GENESIS 5,5 10 270	400 / 50	270	10	670	5,5 / 7,5	66	1150 x 642 x 1837	330	
4152009028	GENESIS 7,5 10 270	400 / 50	270	10	1000	7,5 / 10	66	1150 x 642 x 1837	335	*
4152009031	GENESIS 11 10 270	400 / 50	270	10	1435	11 / 15	69	1150 x 642 x 1837	355	*
4152009034	GENESIS 15 10 270	400 / 50	270	10	1771	15 / 20	69	1150 x 642 x 1837	380	

* Varastotuote

ABAC FORMULA

Ohjelmassa myös Formula-sarjan ruuvikompressorit.
Maksimi teho 30 kW
Maksimi paine 13 bar
Maksimi tuotto 3783 l/min

Lisätietoja tuotteista VelSar-myyjältä.



KOMPRESSORIT

KSE

Teho 2,2 kW

Hiljainen siirrettävä ruuvikompressor säiliöllä.



KSE 2 230



Koodi	Malli	Käyttö- jännite V / Hz	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Melutaso dBA	Mitat l x s x k mm	Paino kg	Varastointi
110012002	KSE 2/100 230	230 / 50	100	10	300	2,2 / 3	60	1218 x 449 x 1011	78	*
110012003	KSE 2/100 400	400 / 50	100	10	270	2,2 / 3	60	1218 x 449 x 1011	78	
110012005	KSE 2 230	230 / 50	-	10	300	2,2 / 3	60	619 x 299 x 509	40	*

* Varastotuote

KPM

Teho 3,5 - 15 kW

Liikuteltava polttomoottori ruuvikompressor
esim. huoltoautoihin.

Honda GX-sarjan polttomoottorit.



Koodi	Malli	Moottori	Säiliö l	Max. paine bar	Tuotto l/min	Teho kW / hp	Startti	Mitat l x s x k mm	Paino kg	Varastointi
150162001	KPM 3,5 AIR TROLLEY	Honda GX 200	8	10	400	3,5 / 4,8	Veto	596 x 730 x 602	55	*
140032001	KPM 4	Honda GX 200	8	10	550	4 / 5,5	Veto	690 x 995 x 996	110	
140172001	KPM 8	Honda GX 390	8	10	1100	7,5 / 10	Sähkö	690 x 1208 x 1088	180	
140182001	KPM 16.5	Honda GX 690	15	10	2100	15 / 20	Sähkö	764 x 1280 x 1223	300	

* Varastotuote